



1. Turn power off.
2. Remove existing fixture and crossbar.
3. Install new crossbar from back of canopy with screws facing down.
4. Pull covered wire in junction box out of box slightly and attach wire to black and white wires from fixture, using wire nuts.
5. Adjust pendant light to desired length before installing. Ideal height is normally 6 to 6 ½ feet from bottom of glass to ground.
6. Attach uncovered wire (ground wire) in box to copper colored wire attached to crossbar with wire nut.
7. Install fixture now by putting wiring back into junction box with transformer. Using small threaded balls, install canopy to the ceiling.
8. Attach glass by screwing it into the pendant socket
9. Check that all connections are correct and that there is no wire exposed.
10. Turn power on and enjoy your fixture

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HAMPSTEAD LIGHTING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HAMPSTEAD LIGHTING IS PROHIBITED.

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±
 ANGULAR: MACH ± BEND ±
 TWO PLACE DECIMAL ±
 THREE PLACE DECIMAL ±

MATERIAL
 FINISH
 DO NOT SCALE DRAWING

	NAME	DATE
DRAWN		
CHECKED		
ENG APPE		
MFG APPE		
Q.A.		
COMMENTS:		

HAMPSTEAD LIGHTING		
INSTALLATION INSTRUCTIONS		
SEE DWG. NO.	Assem1	REV.
SCALE: 1:1		SHEET 1 OF 1